

NMRA Standard	
Layout Command Control™ (LCC)	
Event Transport	
Apr 25, 2021	S-9.7.3.1

Adopted as a NMRA Standard

The OpenLCB Standard document appended to this cover sheet has been formally adopted as a NMRA Standard by the NMRA Board of Directors on the date shown in the *Adopted* column in the *Version History* table below.

Version History

Date	Adopted	Summary of Changes
Feb 17, 2015		Initial version submitted for public comment
Feb 6, 2016	Feb 20, 2016	Minor grammatical corrections and readability improvements
Apr 25, 2021	July 2, 2021	Changed LCC logo to include the ® symbol Changed “Layout Command Control” to have the ™ symbol Added the NMRA Legal Disclaimer fine-print Changed the OpenLCB license to “Creative Commons Attribution-ShareAlike 4.0 International”

Important Notices and Disclaimers Concerning NMRA Standards Documents

The Standards (S), Recommended Practices (RP), Technical Note (TN) and Technical Information (TI) documents of the National Model Railroad Association (“NMRA Standards documents”) are made available for use subject to important notices and legal disclaimers. These notices and disclaimers, or a reference to this page, appear in all standards and may be found under the heading “Important Notices and Disclaimers Concerning NMRA Standards Documents.”

Notice and Disclaimer of Liability Concerning the Use of NMRA Standards Documents

NMRA Standards documents are developed within the Standards and Conformance Department of the NMRA in association with certain Working Groups, members, and representatives of manufacturers and sellers. NMRA develops its standards through a consensus development process, which brings together volunteers representing varied viewpoints and interests to achieve the final product. NMRA Standards documents are developed by volunteers with modeling, railroading, engineering, and industry-based expertise. Volunteers are not necessarily members of NMRA, and participate without compensation from NMRA.

NMRA does not warrant or represent the accuracy or completeness of the material contained in NMRA Standards documents, and expressly disclaims all warranties (express, implied and statutory) not included in this or any other document relating to the standard or recommended practice, including, but not limited to, the warranties of: merchantability; fitness for a particular purpose; non-infringement; and quality, accuracy, effectiveness, currency, or completeness of material. In addition, NMRA disclaims any and all conditions relating to results and workmanlike effort. In addition, NMRA does not warrant or represent that the use of the material contained in NMRA Standards documents is free from patent infringement. NMRA Standards documents are supplied “AS IS” and “WITH ALL FAULTS.”

Use of NMRA Standards documents is wholly voluntary. The existence of an NMRA Standard or Recommended Practice does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the NMRA Standards documents. Furthermore, the viewpoint expressed at the time that NMRA approves or issues a Standard or Recommended Practice is subject to change brought about through developments in the state of the art and comments received from users of NMRA Standards documents.

In publishing and making its standards available, NMRA is not suggesting or rendering professional or other services for, or on behalf of, any person or entity, nor is NMRA undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any NMRA Standards document, should rely upon their own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given NMRA Standards documents.

IN NO EVENT SHALL NMRA BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: THE NEED TO PROCURE SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON ANY STANDARD OR RECOMMENDED PRACTICE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

Translations

NMRA’s development of NMRA Standards documents involves the review of documents in English only. In the event that an NMRA Standards document is translated, only the English version published by NMRA is the approved NMRA Standards document.

Official Statements

A statement, written or oral, that is not processed in accordance with NMRA policies for distribution of NMRA communications, or approved by the Board of Directors, an officer or committee chairperson, shall not be considered or inferred to be the official position of NMRA or any of its committees and shall not be considered to be, nor be relied upon as, a formal position of NMRA.

Comments on Standards

Comments for revision of NMRA Standards documents are welcome from any interested party, regardless of membership. However, **NMRA does not provide interpretations, consulting information, or advice pertaining to NMRA Standards documents.**

Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since NMRA standards represent a consensus of concerned interests, it is important that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, NMRA, its departments, Working Groups or committees cannot provide an instant response to comments, or questions except in those cases where the matter has previously been addressed. For the same reason, NMRA does not respond to interpretation requests. Any person who would like to participate in evaluating comments or in revisions to NMRA Standards documents may request participation in the relevant NMRA working group.

Laws & Regulations


Users of NMRA Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any NMRA Standards document does not constitute compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. NMRA does not, by the publication of NMRA Standards documents, intend to urge action that is not in compliance with applicable laws, and NMRA Standards documents may not be construed as doing so.

Copyrights

NMRA Standards documents are copyrighted by NMRA under US and international copyright laws. They are made available by NMRA and are adopted for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of modeling, structural and engineering practices and methods. By making NMRA Standards documents available for use and adoption by public authorities and private users, NMRA does not waive any rights in copyright to the NMRA Standards documents.

IMPORTANT NOTICE

NMRA Standards documents do not guarantee or ensure safety, security, health, or environmental protection, or ensure against interference with or from other systems, devices or networks. NMRA Standards documents development activities consider research and information presented to the standards development group in developing any safety recommendations. Other information about safety practices, changes in technology or technology implementation, or impact by peripheral systems also may be pertinent to safety considerations during implementation of the standard. Implementers and users of NMRA Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, and interference protection practices and all applicable laws and regulations.



OpenLCB Standard	
Event Transport	
Apr 25, 2021	Adopted

1 Introduction (Informative)

This OpenLCB Standard defines the protocol for transporting OpenLCB events across the OpenLCB network.

2 Intended Use (Informative)

- 5 Transporting events provides general and flexible messaging between nodes, following the principles of the Producer-Consumer model. The information is carried by an Event Identifier (Event ID), a number which in of itself does not have any explicit information. Instead the Event ID is assigned by the user to one specific concept, such as a specific lighting configuration, or a more abstract concept, such as the “start of the day” or “global stop”. That concept can then be
- 10 implemented and shared by cooperative action between nodes that “produce” the event by sending messages, and nodes that “consume” the event by receiving messages and acting upon them. This document defines that interaction between producers and consumers in terms of OpenLCB messages.

- 15 This document describes the required message formats for event transport. Section 4 gives an overview of the message types with an abstract numeric description intended as a normative guide to the construction of concrete message types over specific physical transport media. Section 7 describes in concrete detail the implementation of the event transport message formats for the specific physical transport media that have been adopted as normative standards.

3 References and Context (Normative)

- 20 This standard is in the context of the following OpenLCB Standards:

- The OpenLCB Message Network Standard, which defines the basic messages and how they interact. Higher-level protocols are based on this message network, but are defined elsewhere. The Message Network Standard defines the Initialized node state which is referenced here.
- 25 • The OpenLCB Event Identifiers Standard, which defines the format and content of Event IDs including the class of Well-Known Event IDs and Automatically-Routed Event IDs.
- The OpenLCB CAN Frame Transport Standard, which defines the formats for transporting OpenLCB messages over CAN networks.

4 Message Formats (Normative)

- 30 In the following, the “Common MTI” column specifies the MTI value to be used when communicating in OpenLCB common format. The Common MTI is an abstract numeric

description intended as a normative guide to the construction of concrete message formats over specific physical transport media.

35 “Event ID Range” in the Data Content field refers to a range of Event ID values specified through a compare-under-mask operation. The low bit of the field defines the sign of the mask: a '1' least-significant bit indicates the mask is represented by 1-bits, and similarly for a 0 LSB. The mask is made up of the adjacent identical bits: if the lowest bit is a '0', then all low order contiguous '0' bits will form a mask, while if the lowest bit is a '1', then the low order contiguous '1' bits will form the mask. The remaining upper bits determine the range prefix. To determine whether an Event ID “E” lies within the
40 range “R”, compute:

$$\text{inRange} = ((E \text{ AND NOT mask}) \text{ EQUALS } (R \text{ AND NOT mask}))$$

4.1 Producer/Consumer Event Report (PCER)

Name	Simple Node	Dest ID	Event ID	Common MTI	Data Content
Producer/Consumer Event Report	Y	N	Y	0x05B4	Event ID

45 4.2 Identify Consumer

Name	Simple Node	Dest ID	Event ID	Common MTI	Data Content
Identify Consumer	Y	N	Y	0x08F4	Event ID

4.3 Consumer Identified

Name	Simple Node	Dest ID	Event ID	Common MTI	Data Content
Consumer Identified	N	N	Y	0x04C4 – Valid 0x04C5 – Invalid 0x04C7 – Unknown	Event ID

50 This message has three sub-forms, which carry the status of the identified consumer. They are, respectively:

- Currently valid – the internal state of the consumer & associated devices is known to be the same as if this was the last event consumed
- Currently invalid – the internal state of the consumer & associated devices is known to not be the same as if this was the last event consumed

- 55
- Currently unknown – the consumer cannot determine whether either of the previous conditions is true

4.4 Consumer Range Identified

Name	Simple Node	Dest ID	Event ID	Common MTI	Data Content
Consumer Range Identified	N	N	Y	0x04A4	Event ID Range

- 60
- Nodes shall not emit Consumer Range Identified messages where more than 50% of the Event IDs included in the range are not consumed by the node, except when specified by another OpenLCB Standard.

4.5 Identify Producer

Name	Simple Node	Dest ID	Event ID	Common MTI	Data Content
Identify Producer	Y	N	Y	0x0914	Event ID

4.6 Producer Identified

Name	Simple Node	Dest ID	Event ID	Common MTI	Data Content
Producer Identified	N	N	Y	0x0544 – Valid 0x0545 – Invalid 0x0547-- Unknown	Event ID

65

This message has three sub-forms, which carry the status of the identified producer. They are, respectively:

- 70
- Currently valid – the internal state of the producer & associated devices is known to be that which would cause them to produce the event
 - Currently invalid – the internal state of the producer & associated devices is known to not be the same as that which would cause them to produce the event
 - Currently unknown – the producer cannot determine whether either of the previous conditions is true

4.7 Producer Range Identified

Name	Simple Node	Dest ID	Event ID	Common MTI	Data Content
Producer Identified Range	N	N	Y	0x0524	Event ID Range

75

Nodes shall not emit Producer Range Identified messages where more than 50% of the Event IDs included in the range are not produced by the node, except when specified by another OpenLCB Standard.

4.8 Identify Events

Name	Simple Node	Dest ID	Event ID	Common MTI	Data Content
Identify Events	Y	N	N	0x0970	
	N	Y	N	0x0968	Destination Node ID

80

4.9 Learn Event

Name	Simple Node	Dest ID	Event ID	Common MTI	Data Content
Learn Event	Y	N	Y	0x0594	Event ID

5 States (Normative)

Each consumer and producer of each event has two possible states: “Unadvertised” and “Advertised”.

85 When the node hosting the producer or consumer is not in Initialized state, the consumer or producer shall be in and remain in Unadvertised state.

A producer or consumer of a specific event moves to Advertised state when any of the following happens:

- 90 • The producer or consumer sends a Producer Identified or Consumer Identified, respectively, message containing the Event ID.
- The producer or consumer sends a Producer Range Identified or Consumer Range Identified, respectively, message where the indicated range contains the Event ID.
- Producers and consumers of Event IDs in the Automatically-Routed range are in the Advertised state once the node is in the Initialized state.

95 The messages defined by this Standard shall only be sent when the sending node is in Initialized state.

Producer/Consumer Event Report messages may only be sent when the associated producer is in the Advertised state. OpenLCB equipment may, but is not required to, omit forwarding PCER messages to a consumer of a particular Event ID when that consumer is in Unadvertised state.

100 Consumers and Producers may, but are not required to, have additional state associated with the use of the Learn Event message.

6 Interactions (Normative)

After each transition to Initialized State and before sending a Producer/Consumer Event Report (PCER) message producing a specific Event ID outside the automatically-routed Event ID range, a node shall transition to Advertised state for that Event ID by emitting a Producer Identified or Producer Range Identified message identifying that Event ID.

To ensure receipt of PCER messages, a node consuming a specific Event ID outside the automatically-routed Event ID shall transition to Advertised state for that Event ID by emitting a Consumer Identified or Consumer Range Identified message identifying that Event ID.

6.1 Event Transfer

To produce an event, the node containing the producer shall emit a PCER message containing the specific Event ID. The OpenLCB message network shall transport that message to all attached nodes, except as described in the next paragraph. Nodes containing consumers shall check for a match between the message Event ID and their consumers. If a match is found, the consumer shall perform any local operations configured into it. If a match is not found, the consumer shall not perform any local operations.

Equipment that transports PCER messages shall transport them to all connected nodes from which the equipment has received a Consumer Identified or Consumer Range Identified for the reported Event ID. Equipment that transports PCER messages shall transport all PCER messages containing Event IDs in the automatically-routed range to all connected nodes. Equipment that transports PCER messages may, but is not required to, omit transporting PCER messages with Event ID outside the automatically-routed range to nodes from which the equipment has not received a Consumer Identified or Consumer Range Identified for the reported Event ID.

6.2 Event Inquiry

Upon receipt of either an unaddressed (global) Identify Events message or an addressed Identify Events message addressed to the node, that node shall reply with Producer Identified and/or Producer Range Identified messages covering all non-automatically-routed Event IDs produced by the node, and Consumer Identified and/or Consumer Range Identified messages covering all non-automatically-routed Event IDs consumed by the node.

In response to an unaddressed (global) Identify Events message or an addressed Identify Events message address to the node, that node may but is not required to include Producer Identified and/or Producer Range Identified messages covering automatically-routed Event IDs produced by the node, and Consumer Identified and/or Consumer Range Identified messages covering automatically-routed Event IDs consumed by the node.

6.3 Producer Inquiry

Any node receiving an Identify Producer message that includes a non-automatically-routed Event ID produced by the node shall reply with one or more Producer Identified messages containing that Event ID.

140 Any node receiving an Identify Producer message that includes an automatically-routed Event ID produced by the node may, but is not required to, reply with one or more Producer Identified messages containing that Event ID.

6.4 Consumer Inquiry

Any node receiving an Identify Consumer message that includes a non-automatically-routed Event ID consumed by the node shall reply with one or more Consumer Identified messages containing that Event ID.

145 Any node receiving an Identify Consumer message that includes an automatically-routed Event ID consumed by the node may, but is not required to, reply with one or more Consumer Identified messages containing that Event ID.

6.5 Teach/Learn Configuration

A node may, but is not required to, send a Teach Event message containing an Event ID.

150 A node receiving a Teach Event message may, but is not required to, configure the contained Event ID into some or all of the producers and consumers it contains.

6.6 Resetting to Default

155 Nodes shall ensure that every producer and consumer within the node contains a valid and unique Event ID after the node is reset to defaults. For this purpose, the producers and consumers may contain either well-known Event IDs or Event IDs defined based on this node's unique ID.

If a producer or consumer within the node contains an Event ID based on the node's unique ID, and if that Event ID could have been copied from the node, resetting the node to default shall reconfigure that producer or consumer with a newly-defined Event ID that has not been used before.

7 CAN Adaptation (Normative)

160 There are no specific provisions for CAN transport. The messages are formatted on CAN transport as defined for generic addressed messages in the OpenLCB Message Network Standard.

Table of Contents

1 Introduction (Informative).....	1
2 Intended Use (Informative).....	1
3 References and Context (Normative).....	1
4 Message Formats (Normative).....	1
4.1 Producer/Consumer Event Report (PCER).....	2
4.2 Identify Consumer.....	2
4.3 Consumer Identified.....	2
4.4 Consumer Range Identified.....	3
4.5 Identify Producer.....	3
4.6 Producer Identified.....	3
4.7 Producer Range Identified.....	3
4.8 Identify Events.....	4
4.9 Learn Event.....	4
5 States (Normative).....	4
6 Interactions (Normative).....	5
6.1 Event Transfer.....	5
6.2 Event Inquiry.....	5
6.3 Producer Inquiry.....	5
6.4 Consumer Inquiry.....	6
6.5 Teach/Learn Configuration.....	6
6.6 Resetting to Default.....	6
7 CAN Adaptation (Normative).....	6